



Earth Rod to Tape A Clamps

These clamps are used for joining the earth rod to various sizes of copper or aluminium tape. The clamps have a high resistance to corrosion and are mechanically strong to ensure a lasting connection. The aluminium clamps would mainly be used in lightning protection for connecting aluminium tape to a puddle flange in a lightning protection system.

Nominal Rod Size	Maximum Conductor	L	W	W1	Weight	Pack Qty	Part Number
12.7	26 x 12	51	36	18	0.15	25	ERA 1625
14.2	26 x 12	51	36	18	0.15	25	ERA 1625
	40 x 9	44	51	22	0.25	10	ERA 1638
16	50 x 19	47	69	21	0.25	10	ERA 1650
17.2	31 x 9	43	45	18	0.20	10	ERA 1631
	40 x 6	44	51	22	0.25	10	ERA 1638
20	50 X 15	47	69	21	0.25	10	ERA 1650
25	26 X 6	51	40	25	0.20	10	ERA 2525

All complete with M10 x 25 bolt.

Material:

Clamp Body - Gunmetal or Aluminium Bronze.
Bolt - Phosphor Bronze.

Nominal Rod Size	Maximum Conductor	L	W	W1	Weight	Pack Qty	Part Number
12.7	26 x 12	40	36	18	0.10	25	ERA 1625 SS
14.2	26 x 12	40	36	18	0.10	25	ERA 1625 SS
17.2	26 x 9	40	36	18	0.10	25	ERA 1625 SS

Complete with M10 x 25 bolt.

Material:

Clamp Body - Gunmetal.
Bolt - Stainless Steel.

Nominal Rod Size	Maximum Conductor	L	W	W1	Weight	Pack Qty	Part Number
14.2	30 x 14	46	40	19	0.12	25	ERA 1625 A
17.2	26 x 12	46	40	19	0.12	25	ERA 1625 A

Complete with M10 x 25 bolt.

Material:

Clamp Body - Aluminium.
Bolt - Stainless Steel.

