



## Stranded Copper Conductor

Stranded conductor - Soft drawn.

Manufactured in accordance with BS 6360.

### Bare

Size	Stranding	Weight Per Mtr	Part Number
6	7 / 1.04	0.05	CBS 006
16	7 / 1.70	0.15	CBS 016
25	7 / 2.14	0.23	CBS 025
35	19 / 1.53	0.32	CBS 035
50	19 / 1.78	0.43	CBS 050
70	19 / 2.14	0.62	CBS 070
95	19 / 2.52	0.86	CBS 095
120	37 / 2.03	1.09	CBS 120
150	37 / 2.25	1.33	CBS 150
185	37 / 2.52	1.67	CBS 185
240	61 / 2.25	2.2	CBS 240
300	61 / 2.52	2.76	CBS 300
400	61 / 2.85	3.53	CBS 400

### Green / Yellow PVC Covered

Size	Stranding	Weight Per Mtr	Part Number
6	7 / 1.04	0.05	CPS 006
16	7 / 1.70	0.15	CPS 016
25	7 / 2.14	0.23	CPS 025
35	19 / 1.33	0.32	CPS 035
50	19 / 1.78	0.43	CPS 050
70	19 / 2.14	0.62	CPS 070
95	19 / 2.52	0.86	CPS 095
120	31 / 2.03	1.09	CPS 120
150	37 / 2.25	1.33	CPS 150
185	37 / 2.52	1.67	CPS 185
240	61 / 2.25	2.2	CPS 240
300	61 / 2.52	2.76	CPS 300
400	61 / 2.85	3.53	CPS 400

### Material:

Copper.

